


## Designed for use subsea, and operated with ROV.

### Description:

ROV Hot-Stabs and Receptacles are used to power hydraulic tools, transfer fluid, perform chemical injections, and to monitor pressure. The Hot-Stab front is made of a softer material than super duplex (JM7) to avoid damaging the receptacle. The Hot-Stab and receptacle are equipped with double acting check valve with setting; inflow and outflow 1 bar. All parts designed to withstand 690 bar working pressure, down to 3000msw.

### Specification:



	Hot-Stab	Receptacle	Pressure-Stab	Protection-Stab
Depro drawing:	DEP-GA-0111	DEP-GA-0120	DEP-GA-0255	DEP-GA-0529
API standard:	17D	17D	17D	17D
Diameter stab:	35mm	N/A	35mm	35mm
Max pressure:	690 bar	690 bar	690 bar	0 bar
Connection:	3/8" - BSP	3/8" - BSP	N/A	N/A
Temperatur Min/max:	0-110dgC	0-110dgC	0-110dgC	0-60dgC
Material body:	1.4410-SuperDuplex	1.4410-SuperDuplex	1.4410-SuperDuplex	JM/OM7
Seal material:	HPUN270	N/A	HPUN270	N/A
Max water dept:	3000 m	3000 m	3000 m	3000 m
Weight in air:	3,05Kg	1,6Kg	3,05Kg	2,7Kg
Dimensions LxØ (Body):	421x70mm	66x79mm	394x70mm	394x70mm

Adjustable configuration and setup based on fluid media, flow, working pressure, check valve setting, and material for longer use subsea available on request.