

## Designed for use subsea, and operated with ROV.

### Description:

Type B ROV Hot-Stabs and Receptacles are used to power hydraulic tools, transfer fluid, perform chemical injections, and to monitor pressure. The Hot-Stab front is made of a softer material than super duplex (JM7) to avoid damaging the receptacle. The Hot-Stab and receptacle are equipped with double acting check valve with setting; inflow and outflow 1 bar. All parts designed to withstand 690 bar working pressure, down to 3000msw.



### Specification:

	Hot-Stab	Receptacle	Pressure-Stab	Protection-Stab
Depro drawing:	DEP-GA-0125-A	DEP-GA-0122	DEP-A-0130	DEP-GA-0535
ISO standard:	13628-8	13628-8	13628-8	13628-8
API standard:	17H	17H	17H	17H
Diameter stab:	43mm	N/A	43mm	43mm
Max pressure:	690 bar	690 bar	690 bar	0 bar
Connection:	3/8" - BSP	3/8" - BSP	N/A	N/A
Temperatur Min/max:	0-110dgC	0-110dgC	0-110dgC	0-60dgC
Material body:	1.4410-SuperDuplex	1.4410-SuperDuplex	1.4410-SuperDuplex	JM/OM7
Seal material:	HPUN270	N/A	HPUN270	N/A
Max water dept:	3000 m	3000 m	3000 m	3000 m
Weight in air:	4,70 Kg	3,67 Kg	4,50 Kg	4,5 Kg
Dimensions LxØ (Body):	503x70mm	155x80mm	463x70mm	413x70mm

Adjustable configuration and setup based on fluid media, flow, working pressure, check valve setting, and material for longer use subsea available on request.