

Designed for use subsea, and operated with ROV.

Description:

ROV Hot-Stabs and Receptacles are used to power hydraulic tools, transfer fluid, perform chemical injections, and to monitor pressure. The Hot-Stab front is made of a softer material than the main body to avoid damaging the receptacle. The hot stab and receptacle are equipped with double acting check valve with setting; inflow and outflow 1 bar. All parts designed to withstand 690 bar working pressure, down to 3000msw.



Specification:

Hot-Stab Receptacle Pressure-Stab Protection-Stab

Depro drawing:	DEP-GA-0115	DEP-GA-118	DEP-GA-0532	DEP-GA-0533
API standard:	17D	17D	17D	17D
Diameter stab:	35mm	N/A	35mm	35mm
Max pressure:	690 bar	690 bar	690 bar	0 bar
Connection:	3/8" - BSP	3/8" - BSP	N/A	N/A
Temperatur Min/max:	0-110 dgC	0-110 dgC	0-110 dgC	0-60 dgC
Material body:	1.4410-SuperDuplex	1.4410-SuperDuplex	1.4410-SuperDuplex	JM/OM7
Seal material:	HPUN270	N/A	HPUN270	N/A
Max water dept:	3000 m	3000 m	3000 m	3000 m
Weight in air:	4,53 Kg	4,68 Kg	4,60 Kg	4,3 Kg
Dimensions LxØ (Body):	472x70mm	168x79mm	432x70mm	432x70mm

Adjustable configuration and setup based on fluid media, flow, working pressure, check valve setting, and material for longer use subsea available on request.