DEPRO HPU-207bar@50l/min DEP-DS-DSH-00101/01

HPU with 5 proportionally controlled functions

Description:

Depro's portable and powerful Hydraulic Power Unit deliver the power you need in a convenient, lightweight package. The durable design provides superior control and produces less heat and noise than typical hydraulic power units. A proportional load sensing valve with 5 functions provides requested hydraulic power throughout the adjustable range to the consumers. Unit includes a complete filtration package with pressure, return and circulation filter and water removal unit to ensure the hydraulic fluid at all time is kept at the cleanest level possible and a water cooler to ensure low fluid temperature.





Specification:

- Depro drawing: DEP-GA-0991
- Working pressure: 207 bar (3000 PSI)
- Max oil flow: 50 liter / minute
- Independent hydraulic lines: 5
- Oil Reservoir: 160 liters
- 5 micron filtration
- Connection type port 1: 1/2 inch BSP
- Connection type port 2-5: 1/2 inch Snap-Tite 71 •

- Motor: 18,5kW,
- Electrical interface
 - 400V / 3 phase / 50Hz / 33,5A (Socket 63A)
 - 690V / 3 phase / 50Hz / 19,4A (Socket 63A)
 - 440V / 3 phase / 60Hz / 33,5A (Socket 63A)
- Dimension (LxWxH): 1200x800x1370mm
- Weight in air: 860 Kg
- Pad Eye: Ø20 for Shackle 3,25t
- Certified to: DNVGL ST E273, R00